



SPECIFICATION



Net Weight: 95g ± 5g

Part No.	Rated Voltage (V)	Speed (RPM)	Current (Amp)	Voltage Range (V)	Air Flow (CFM)	Static Pressure (inch-H ₂ O)	Noise (dBA)	Bearing	Life Expectancy (@25°C / Hour)
HS-9225-S12L	12	1800	0.12	07~15	37.4	0.16	24	Sleeve	21,000
HS-9225-B12L								One Ball & One Sleeve	81,000
HS-9225-D12L								Dual Balls	86,000
HS-9225-S12M	12	2400	0.16	07~15	46.6	0.23	29	Sleeve	20,600
HS-9225-B12M								One Ball & One Sleeve	78,000
HS-9225-D12M								Dual Balls	83,000
HS-9225-S12H	12	3000	0.22	07~15	55.6	0.26	34	Sleeve	20,000
HS-9225-B12H								One Ball & One Sleeve	75,000
HS-9225-D12H								Dual Balls	80,000
HS-9225-S24L	24	1800	0.10	15~27	37.4	0.16	24	Sleeve	21,000
HS-9225-B24L								One Ball & One Sleeve	81,000
HS-9225-D24L								Dual Balls	86,000
HS-9225-S24M	24	2400	0.12	15~27	46.6	0.23	29	Sleeve	20,600
HS-9225-B24M								One Ball & One Sleeve	78,000
HS-9225-D24M								Dual Balls	83,000
HS-9225-S24H	24	3000	0.16	15~27	55.6	0.26	34	Sleeve	20,000
HS-9225-B24H								One Ball & One Sleeve	75,000
HS-9225-D24H								Dual Balls	80,000

★ High Pace reserve the rights to change data without notice.

★ Custom specifications are available on request.